CABS Busbar Support Kit - CABS4-5TN-600 (549260)












- For all busbar types and ERIFLEX ERILINK busducts
- Improve bending resistance by interlocking or stacking two profiles
- Quick and easy to install
- Halogen free insulators
- RoHS compliant







Part Number	CABS4-5TN-600
Article Number	549260
Material	Aluminum Glass Fibre Reinforced Polyamide Steel
Finish	Electrogalvanized
Typical Application Current Rating	400 – 4,500 A
Max Working Voltage, IEC (Ui)	1,000 VAC 1,500 VDC
Working Temperature	-40 to 130 °C
Complies With	IEC® 60439.1 IEC® 61439.1
Flammability Rating	UL® 94V-0
Busbars per Phase	1 – 4
Busbar Width	30 – 125 mm
Busbar Thickness	5 mm
Depth (D)	39 mm
Width (W)	550 mm
A	500 mm
В	75 – 125 mm
С	525 mm
Unit Weight	0.84 kg
Certifications	Bureau Veritas 41941 BV CE EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports RoHS





Part Number	CABS4-5TN-600
Standard Packaging Quantity	1 pc
UPC	78285687570
EAN-13	3479775492605

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



