Universal Busbar Support - UBS2-10T (551080)













- Universal fixing system
- Installs quickly and easily
- Extremely robust construction
- Adjustable arms for easy mounting
- Halogen free insulators







To the state of th	
Part Number	UBS2-10T
Article Number	551080
Material	Glass Fibre Reinforced Polyamide Steel
Max Working Voltage, IEC (Ui)	1,000 VAC 1,500 VDC
Working Temperature	-40 to 130 °C
Complies With	IEC® 60439.1 IEC® 61439.1
Flammability Rating	UL® 94V-0
Typical Application Current Rating	3,600 A
Busbars per Phase	1 – 2
Busbar Width	30 – 120 mm
Busbar Thickness	10 mm
Width (W)	375 – 575 mm
А	350 – 550 mm
В	176 mm
С	307 mm
D	110 mm
Unit Weight	2.18 kg
Certifications	Bureau Veritas 41941 BV CE EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports RoHS





Part Number	UBS2-10T
Standard Packaging Quantity	1 рс
UPC	78285687616
EAN-13	3479775510804

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



