


BSC-125A Four Pole Insulating Support – BSC-125A (551321)



- Create custom four pole distribution blocks for an electrical distribution system
- Protection screen can be attached directly to the support
- Includes screws to mount threaded copper busbars
- Easily clips onto DIN rail or mounts to panel with screws
- Halogen free
- RoHS compliant



Part Number	BSC-125A
Article Number	551321
Material	Glass Fibre Reinforced Polyamide Steel
Finish	Electrogalvanized
Max Working Voltage, IEC (Ui)	630 VAC 630 VDC
Working Temperature	-40 to 130 °C
Typical Application Current Rating	125 - 160 A
Complies With	IEC® 60439.1 IEC® 61439.1
Flammability Rating	UL® 94V-0
Busbar Width	12 - 15 mm
Busbar Thickness	4 - 5 mm
Depth (D)	76 mm
Height (H)	120 mm
Screw Diameter (Sc)	M6
Unit Weight	0.1 kg
Certifications	CE EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports RoHS

Part Number	BSC-125A
Standard Packaging Quantity	10 pc
UPC	78285687624
EAN-13	3479775513218

Must be used with copper busbars.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.