





# FS Spacer Clamp – FS80-100 (553580)



- Provides support for ERIFLEX FLEXIBAR and insulated braided conductors without damaging the insulation
- Ensures correct spacing for optimum cooling
- Supports up to four conductors in parallel
- Easy to install
- Spacers are halogen free
- RoHS compliant



Part Number	FS80-100
Article Number	553580
Finish	Electrogalvanized
Material	Polyamide Steel
Working Temperature	-40 to 130 °C
Flammability Rating	UL® 94HB
Conductor Width	80 – 100 mm
Height (H)	140 mm
Length (L)	224 mm
Hole Size (HS)	8.5 mm
A	200 mm
Unit Weight	0.25 kg
Certifications	EAC 8546901000 (Russian Federation) RoHS UR
Standard Packaging Quantity	10 pc
UPC	78285657833
EAN-13	3479775535807

Recommended distance between supports is 400 mm (15 3/4").

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.