UFS ERIFLEX FLEXIBAR and IBSB Support Kit – UFS-KIT (553590)












- Kit includes one rail and 24 retaining blocks
- Create up to three 650 mm (25.6") supports capable of holding four ERIFLEX FLEXIBAR
- Retaining blocks are halogen free
- RoHS compliant





Part Number	UFS-KIT
Article Number	553590
Material	Aluminum Polyamide
Conductor Thickness	2 – 10 mm
Conductor Width	15.5 – 120.0 mm
Height (H)	57.5 mm
Length (L)	2 m
Width (W)	30 mm
A	24 mm
В	15 mm
Unit Weight	2.3 kg
Certifications	EAC 8546901000 (Russian Federation) RoHS UR
Standard Packaging Quantity	1 рс
UPC	78285644975
EAN-13	3479775535906

Recommended distance between supports is 400 mm (15 3/4").





UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



