

# SBS Isolating Silicone Sleeve – SBS-25 (554070)



- Resistant to high temperature
- Cost effective sleeve for insulation
- High flexibility
- Halogen free



Part Number	SBS-25
Article Number	554070
Material	Fiberglass Silicone
Insulation Voltage	2.5 kV
Max Working Voltage, IEC (Ui)	690 VAC/DC
Max Working Voltage, UL (Vin)	690 VAC/DC
Working Temperature	-60 to 220 °C
Flammability Rating	UL® 1441 VW-1
Diameter	25 mm
Length	30 m
Unit Weight	0.185 kg
Certifications	RoHS UR
Standard Packaging Quantity	30 m
UPC	78285667145
EAN-13	3479775540702

Unit weight is per meter [3.28'].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.