

# PDBS Polyamide Braided Sleeve – PDBS10G (554460)



- Expandable cabling sleeves for many applications
- Flexible bundling and mechanical protection of electrical cables and wires
- Packed in easy dispense boxes
- Halogen free
- RoHS compliant



Part Number	PDBS10G
Article Number	554460
Material	Polyamide
Color	Gray
Working Temperature	-40 to 120 °C
Density	1.14 kg/m3
Flammability Rating	UL® 94V-2
Diameter	10 mm
Length	100 m
Unit Weight	0.014 kg
Certifications	RoHS
Standard Packaging Quantity	100 m
UPC	78285657836
EAN-13	3479775544601

Part Number	Coverage Efficiency					
	Diameter					
	Nom	Coverage	Min	Coverage	Max	Coverage
PDBS5x	5 mm	97%	4 mm	100%	8 mm	90%
PDBS8x	8 mm	94%	6 mm	100%	10 mm	91%
PDBS10x	10 mm	95%	8 mm	100%	14 mm	94%
PDBS12x	12 mm	96%	10 mm	100%	16 mm	94%
PDBS16x	16 mm	96%	14 mm	100%	18 mm	98%
PDBS20x	20 mm	95%	16 mm	100%	25 mm	99%
PDBS30x	30 mm	90%	20 mm	100%	35 mm	92%
PDBS40x	40 mm	90%	30 mm	100%	45 mm	94%
PDBS50x	50 mm	95%	40 mm	100%	65 mm	100%
PDBS70x	70 mm	94%	60 mm	100%	80 mm	99%

Unit weight is per meter [3.28'].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.