


# FGBS Fiberglass Braided Sleeve – FGBS4 (556200)



- Fiberglass impregnated with high temperature varnish
- Resistant to high temperature
- Thermal insulation and mechanical protection
- Halogen free



Part Number	FGBS4
Article Number	556200
Material	Fiberglass
Working Temperature	-70 to 400 °C
Flammability Rating	UL® 1441 VW-1
Diameter	12 mm Max 4 mm Nom
Length	100 m
Unit Weight	0.01 kg
Certifications	RoHS
Standard Packaging Quantity	100 m
UPC	78285667149
EAN-13	3479775562001

Unit weight is per meter [3.28'].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.