

Flexbus Fleksibel		Dimensjoner					Strømføringsevne						De-rating	
El. nr.	Tverrsn.	A mm	B mm	C mm	D mm	E mm	Vekt Kg/Mtr.	20 gr. C ΔT 70 K	30 gr. C ΔT 60 K	40 gr. C ΔT 50 K	50 gr. C ΔT 40 K	60 gr. C ΔT 30K		
1710330	220 mm ²	9,0	50	50	16	58	1,25	719 A	666 A	606 A	546 A	473 A	2	2,85
1710331	360 mm ²	12,3	50	50	21	58	1,85	973 A	901 A	820 A	739 A	640 A	2	2,80
1710332	545 mm ²	18,0	50	50	31	58	2,60	1217 A	1127 A	1026 A	924 A	800 A	2	2,77
1710333	640 mm ²	21,3	50	50	31	58	2,95	1332 A	1233 A	1122 A	1011 A	875 A	2	2,75
1710334	800 mm ²	13,0	100	100	28	108	3,72	1656 A	1533 A	1395 A	1257 A	1088 A	2	2,71
1710335	960 mm ²	14,8	100	100	28	108	4,45	1902 A	1761 A	1603 A	1444 A	1250 A	2	2,71
1710336	1280 mm ²	18,0	100	100	31	108	5,70	2143 A	1984 A	1805 A	1627 A	1409 A	2	2,70
1710337	1810 mm ²	25,0	100	100	39	108	7,75	2544 A	2356 A	2144 A	1932 A	1673 A	2	2,70

