

Flexbus Fleksibel Skinnepakke		Strømføringsevne			
El. nr.	Tverrsnitt per fase	20 gr. C ΔT 70 K	30 gr. C ΔT 60 K	40 gr. C ΔT 50 K	50 gr. C ΔT 40 K
<u>2871536</u>	2 x 1810 mm ²	5088 A	4712 A	4288 A	3864 A
<u>2871517</u>	2 x 1280 mm ²	4286 A	3968 A	3610 A	3524 A
<u>2871520</u>	2 x 960 mm ²	3804 A	3522 A	3206 A	2888 A
<u>2871530</u>	2 x 800 mm ²	3312 A	3066 A	2790 A	2514 A
<u>2871544</u>	2 x 640 mm ²	2664 A	2466 A	2244 A	2022 A
<u>2871535</u>	1 x 1810 mm ²	2544 A	2356 A	2144 A	1932 A
<u>2871524</u>	2 x 545 mm ²	2434 A	2254 A	2052 A	1848 A
<u>2871516</u>	1 x 1280 mm ²	2143 A	1984 A	1805 A	1627 A
<u>2871543</u>	2 x 360 mm ²	1946 A	1802 A	1640 A	1478 A
<u>2871519</u>	1 x 960 mm ²	1902 A	1761 A	1603 A	1444 A
<u>2871529</u>	1 x 800 mm ²	1656 A	1533 A	1395 A	1257 A
<u>2871538</u>	2 x 220 mm ²	1428 A	1332 A	1212 A	1092 A
<u>2871540</u>	1 x 640 mm ²	1332 A	1233 A	1122 A	1011 A
<u>2871523</u>	1 x 545 mm ²	1217 A	1127 A	1026 A	924 A
<u>2871542</u>	1 x 360 mm ²	973 A	901 A	820 A	739 A
<u>2871527</u>	1 x 220 mm ²	719 A	666 A	606 A	546 A