

UTVALGSTABELL

Enpoledede Distribusjonsblokker - UD, UDJ, UDF

SINGLE POLE DISTRIBUTION BLOCKS (UD SERIES) – QUICK SELECTION GUIDE

Part number	Terratech El.nummer	Typical IEC Current	Line side: Nbre of connection	Line side Min and Max conductor size	Load side: Nbre of connection	Load side Min and Max conductor size	Max working voltage IEC	Max working voltage UL
UD-80A	1223515	80 A	 1 Cable	6–16 mm ²	 6 Cables	2.5–16 mm ²	1,000 VAC/DC	600 VAC/DC
UDJ-125A	1223516	125 A	 1 Cable	10–35 mm ²	 7 Cables	2.5–16 mm ²	1,000 VAC/DC	600 VAC/DC
UDJ-160A	1223517	160 A	 1 Cable	10–70 mm ²	 7 Cables	2.5–16 mm ²	1,000 VAC/DC	600 VAC/DC
UD-250A	1223518	250 A	 1 Cable	35–120 mm ² I	 11 Cables	2.5–35 mm ²	1,000 VAC/DC	600 VAC/DC
UDF-250A	1223519	250 A	 Flat Leder	Flexibar 3X9X0.8–6x15.5x0.8	 6 Cables	2.5–16 mm ²	1,000 VAC/DC	600 VAC/DC
UD-400112AL	1223529	400 A	 1 Cable	95–185 mm ²	 12 Cables	2.5–10 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD-400112CU	1223522	400 A	 1 Cable	96–185 mm ² I	 12 Cables	2.5–10 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD-400212AL	1223528	400 A	 2 Cables	35–95 mm ²	 12 Cables	2.5–10 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD-400212CU	1223521	400 A	 2 Cables	35–95 mm ²	 12 Cables	2.5–10 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD-400A	1223520	400 A	 1 Cable	95–185 mm ²	 11 Cables	2.5–35 mm ²	1,000 VAC/DC	600 VAC/DC
UDF-500A	1223523	500 A	 Flat Leder	Flexibar 4x15.5x0.8–8x24x1	 11 Cables	2.5–35 mm ²	1,000 VAC/DC	600 VAC/DC
UD6C500AL	1202390	500 A	 1 Cable	95–240 mm ²	 6 Cables	10–50 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UDF6C500AL	1202391	500 A	 Flat Leder	Flexibar 2x20x1–10x24x1 Isolert Kobberlisse F50-F100	 6 Cables	10–50 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UDF9C500AL	1202392	500 A	 Flat Leder	Flexibar 2x20x1–10x24x1 Isolert Kobberlisse F50-F100	 9 Cables	4–25 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UDF12C500AL	1202393	500 A	 Flat Leder	Flexibar 2x20x1–10x24x1 Isolert Kobberlisse F50-F100	 12 Cables	4–25 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD9C630AL	1202394	630 A	 1 Cable	120–300 mm ²	 9 Cables	4–25 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD2C12C630AL	1202395	630 A	 2 Cables	95–185 mm ²	 12 Cables	4–25 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UDF12C800AL	1202396	800 A	 Flat Leder	Flexibar 2x20x1–10x32x1 Isolert Kobberlisse F50-F240	 12 Cables	4–25 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD2C12C1000AL	1202397	1000 A	 2 Cables	35–240 mm ²	 12 Cables	4–25 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UDF9C1000AL	1202398	1000 A	 Flat Leder	Flexibar 6x24x1–10x50x1 Isolert Kobberlisse F120-F240	 9 Cables	10–95 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC
UD2C9C1250AL	1202399	1250 A	 2 Cables	185–400 mm ²	 9 Cables	10–95 mm ²	1,000 VAC, 1,500 VDC	1,000 VAC/DC